



ELECTRIC BUTTON
ATTACHING SEWING MACHINE

CC-438D

电脑钉扣机

高速缝纫且线迹美观，实现了优良的缝纫品质和高生产效率。

It has the high speed sewing and perfect line tracks, superior quality sewing and high effective.

转速为2,700rpm
缝制范围最大6.4~6.4 mm
压脚上升最大13mm
半回转标准旋梭
已输入49种缝纫图案

Sewing speed :2700rpm
The largest sewing area: 6.4~6.4 mm
The max height of presser:13mm
Sway hook
90 patterns has been saved in the machine

规格 Specification

型号 / Model	CC-438D
线迹样式 / Stitch Pattern	单针平缝 / single-needle flat seam
最高缝纫速度 / Maximum Sewing Speed	2700rpm
缝制区域(x-y) / Sewing Area (x-y)	最大40×30 mm / Maximum 40×30mm
送布方式 / Fabric Feeding Method	Y-间歇送布 (脉冲马达驱动方式) / Y-\$interval fabric feeding (impulse motor driven mode)
针距 / Needle Pitch	0.05 ~ 12.7 mm
针数 / Gauge	任意 (关于输入完成的图案缝纫, 参照“程序一览”) Random (about the sewing of the pattern after finishing the input, refer to “Summary of Programs”)
最大针数 / Maximum Gauge	210,000针 (包括增加针数200,000针) / 210,000 needles (including increased 200,000 needles)
抬压脚方式 / Presser Lifter Mode	脉冲马达驱动方式 / Impulse motor driven mode
压脚上升量 / Presser Lifting Amount 纽扣夹上升量 / Button Grip Lifting Amount	最大13mm/ Maximum 13mm
使用旋梭 / Rotating Shuttle	半回转标准旋梭 (2倍旋梭另售) Semi-rotary standard rotating shuttle (double rotating shuttle is sold separately)
扫线装置 / Thread Sweeping Device	标准装备 / Standard device
切线装置 / Thread Cutting Device	标准装备 / Standard device
夹线装置 / Thread Clamping Device	标准装备 / Standard device
数据存储方式 / Data Storage Mode	闪存 (使用CF卡可增加任意缝纫图案) Flash memory (with CF card, it can increase any sewing pattern as will)
用户程序数 / Number Of User's Programs	50
循环程序数 / Number Of Cycle Programs	9个循环 (各15个程序) / 9 cycles (15 programs for each)
存储数据数 / Number Of Stored Data	已输入89种缝纫图案 / It has already input 89 kinds of sewing patterns (最多可以增加缝制数据200种。增加总针数约在200,000针以内) (It can add 200 kinds of sewing data at the most. Increased total gauge is within 200,000 needles)
马达 / Motor	AC伺服马达550W / AC servo motor 550W
重量 / Weight	机头: 约 56kg、操作盘: 约 0.6kg / Machine head: about 56kg, operation panel: about 0.6kg 控制箱: 14.2 ~ 16.2kg (因提供地区而异) / Control box: 14.2 ~ 16.2kg (vary from region to region)
电源 / Power	单相100V/220V / Single-phase 100V/220V 三相200V/220V/380V/400V 400VA / Three-phase 200V/220V/380V/400V 400VA
净重/N.W	150
毛重/G.W	200
包装尺寸/Measurement	1250*850*1350
体积/CBM	1.44m ³